



Features

- Made of lightweight double anodized aluminum
- Frosted lens protects light source while evenly diffusing light
- Field cuttable extrusion and lenses
- Aluminum provides excellent heat dissipation
- End caps available for a tailored look
- Compatible with most Trulux Tape Light

Available Lengths

39-3/8" (1 meter)

Available Finishes



Anodized Aluminum

Compatible Tape Light

- Trulux Single Color
- Trulux Tunable CCT
- Trulux RGB / RGBW / RGB+TW

TRULUX™ Turbo Extrusion

Resembling a low profile T5 luminaire, the Turbo extrusion allows for side by side tape light mounting to provide ample light output when needed. Available in with round and square lens profiles, create surface mount tape light based fixtures to be used in dynamic applications or general ambient lighting purposes.

Best suited applications:

Offices, closets, food prep areas, workshops, and shelving

Ordering Information

PE-TURBO2-1M*	Turbo Aluminum Extrusion
PE-RTURBO-1M*	Round Frosted Acrylic Lens
PE-QTURBO-1M*	Square Frosted Acrylic Lens
PE-RTURBO2-END*	Turbo Round End Cap
PE-QTURBO2-END*	Turbo Square End Cap

*Turbo Extrusion is available as special order only. Please allow up to 2 weeks for order processing.

